Slotted set screws with cone point (ISO 7434: 1983)

English version of DIN EN 27 434

DIN EN 27 434

This standard incorporates the English version of ISO 7434.

Gewindestifte mit Schlitz und Spitze (ISO 7434: 1983)

Supersedes DIN 553. September 1986 edition

European Standard EN 27 434 : 1992 has the status of a DIN Standard.

A comma is used as the decimal marker.

National foreword

The publication of this standard is in keeping with a decision made by CEN/TC 185 to adopt, without afteration, a series of ISO Standards covering slotted set screws as European Standards. The responsible German body involved in their publication is the Normenausschuß Mechanische Verbindungselemente (Fasteners Standards Committee).

As a consequence, all DIN Standards covering such screws have been superseded by the corresponding DIN EN Standards

EN Standard	DIN EN Standard	Title	Previous DIN Standard
24 766	24 766	Slotted set screws with flat point	
27 434	27 434	Slotted set screws with cone point	551
27 435	27 435	Slotted set screws with long dog point	553
27 436	27 436	Slotted set screws with rup point	417 438

It may be assumed that the differences in the specifications made here and those of the superseded DIN Standard will not give rise to any problems regarding interchangeability of slotted set screws (except for screws of size M 1.2). See National appendix for guideline values for the mass of slotted set screws not given in the European Standard. In clause 2, ISO Standards 3269 and 4042 are referred to as being at the stage of draft. These standards have since been

The DIN Standards corresponding to the ISO Standards referred to in clause 2 of the EN are as follows:

ISO Standard DIN Standard

ISO 225

DIN EN 20 225

ISO 3269

DIN ISO 3269 (at present at the stage of draft) DIN ISO 3506 (at present at the stage of draft) ISO 3506

ISO 4042

DIN ISO 4042 ISO 4759-1

DIN ISO 4759 Part 1 The DIN 4000-2-3 tabular layout of article characteristics applies for screws as covered here.

> Continued overleaf. EN comprises 5 pages.

Page 2 DIN EN 27 434

Standards referred to

(and not included in References)

DIN 4000 Part 2 Tabular layout of article characteristics for bolts, screws and nuts

DIN EN 20 225 Bolts, screws, stude and nuts; symbols and designations for dimensioning

Previous editions

DIN 533: 10.22, 05.24, 06.37x, 02.53, 02.72, 09.86.

Amendments

- In comparison with DIN 553, September 1986 edition, the following amendments have been made.
- a) Thread sizes M 1 and M 1,4 have been dropped, as have been the specifications for surface roughness.
- b) Guideline values for the mass of set screws have been given in a National appendix.
 c) Tolerance 6 g has been specified for the thread diameter.
- d) M 1.2 set screws shall be of product grade A.
- e) Property class 22H set screws need not be thermally blackened any longer,
- f) The standard designation has been changed.

International Patent Classification

F 16 B 035/00

F 16 B 023/00

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN 27 434

July 1992

UDC 621.882.219.71.092.5

Descriptors: Fasteners, screws, set screws, dimensions, specifications, dimensional tolerances, designation.

English version

Slotted set screws with cone point (ISO 7434: 1983)

Vis sans tête, fendues, à bout pointu (ISO 7434 : 1983)

Gewindestifte mit Schlitz und Spitze (ISO 7434 : 1983)

This European Standard was approved by CEN on 1982-07-17 and is identical to the ISO Standard as referred to. CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any afteration.

Up-to-date fists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Denmark, Finland, France, Germany, Greece, Iceland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

CEN

European Committee for Standardization Comité Européen de Normalisation Europäisches Komitee für Normung

Central Secretariat: rue de Stassart 36, B-1050 Brussels

Foreword

In 1992, CEN/TC 185 'Threaded and unthreaded festeners and accessories', the Secretariat of which is held by DIN, decided to submit International Standard

ISO 7434: 1983. Slotted set screws with cone point

to Formal Vote. The result was positive.

In the countries bound to implement this European Standard, a national standard identical to this European Standard shall be published, and conflicting national standards withdrawn, by 1993-01-31 at the latest.

In accordance with the CEN/CENELEC Internal Regulations, the following countries are bound to implement this European Standard: Austria, Belgium, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

Endorsement notice

The text of the International Standard ISO 7434 : 1983 was approved by CEN as a European Standard without any modification.

Scope and field of application

This International Standard specifies the characteristics of slotted set screws with cone point and thread sizes from M 1,2 to M 12 inclusive and product grade A.


If other specifications are required, it is recommended that they should be selected from existing International Standards, for example ISO 261, ISO 888, ISO 898, ISO 965, ISO 3506, ISO 4759/1.

2 References

- ISO 225, Fasteners Bolts, screws, study and nuts Symbols and designations of dimensions.
- ISO 261, ISO general purpose metric screw threads General plan.
- ISO 888, Bolts, screws and studs Nominal lengths, and thread lengths for general purpose bolts.
- ISO 898, Mechanical properties of fasteners.
- ISO 965, ISO general purpose metric screw threads Tolerances.
- ISO 3269, Fasteners Acceptance inspection, 11
- ISO 3506, Corrosion-resistant stainless steel fasteners Specifications.
- ISO 4042, Threaded components Electroplated coatings components.13
- ISO 4753, Fasteners Ends of parts with external metric ISO thread.
- ISO 4759/1. Tolerances for lasteners Part 1: Bolts, screws and nuts with thread diameters > 1,6 and < 150 mm and product grades A, B and C.

At present at the stage of draft.

3 Dimensions



- The 120° angle is mendatory for short length screws above the dotted stepped line.
- The 90° angle applies only to the portion of the point below the root diameter of the thread with nominal lengths / below the dotted stepped line.
- For short length screws above the dotted stepped line a 120° angle is mandatory.

	d size d		M 1,2	M 1,6	M 2	M 2.5	M 3	(M 3,5)17	M 4	M 5	M 6	M 8	M 10	millimetre
P ²⁾			0.25	0,35	0,4	0,45	0,5	0,6	0,7	0,8	1	1,25		M 12
d_f		72		Minor thread diameter										1,75
d, 3)		min.	-	-	_	T -		T -	T	Ť <u>-</u>	T_		1	
-,		max.	0,12	0,16	0,2	0,25	0,3	0,35	0,4	0,5	1,5	<u> </u>		
		nom.	0,2	0,25	0,25	0,4	0.4	0,5	0,6	0,8	1,3	2	2,5	3
п		min.	0,26	0,31	0,31	0,46	0,46	0,56	0,66	0,86	1,06	1,2	1,6	2
		max.	0,4	0,45	0,45	0,6	0,6	0,7	0,8	1	1,00	1,26	1,66	2,06
,		min.	0,4	0,56	0,64	0.72	0,8	0.96	1,12	1,28	1,6	1,51	1,91	2.31
<u>. </u>		max.	0,52	0,74	0,84	0,95	1,05	1,21	1,42	1,63	2	2	2,4	2,8
										1,00	1	2,5	3	3,6
	/11. 4) 1													
пот.	min.	max.												
2	1,8	2,2										Γ		
2,5	2,3	2,7												
3	2,8	3,2												
4	3,7	4,3			1									
5	4,7	5,3					-							
6	5.7	6,3												
8	7,7	8,3												
10	9,7	10.3				Ra	nge				4			
12	11,6	12.4						ı e						
14)	13,6	14,4				- 1		cam	mercial				<u>i</u> }	
16	15,6	16,4			_					length				
20	19,6	20.4												
25	24,6	25,4												
30	29,6	30,4												
35	34,5	35,5												
40	39,5	40,5												
45	44.5	45,5												
50	49,5	50.5		I										
55	54,4	55,6								-	-			
50	59.4	60,6												

- Sizes in brackets should be avoided if possible.
- P = pitch of the thread.
- < M5 no flat part on the cone required; the point may be slightly rounded.
- 4) Min. and max, values according to ISO 4759/1, but rounded to one decimal place.

4 Specifications and reference International Standards

Material		Stoel	T						
_	Talana	3/06/	Stainless steel	Non-ferrous metal					
Thread	Tolerance	- 6g							
	International Standards	ISO 261, ISO 965							
Mechanical properties	Property class	14H, 22H	A1 - 50						
	International Standards	ISO 898/5		1)					
Tolerances	Product grade	100 00075	ISO 3506						
			A						
	International Standard	ISO 4759/1							
		Plain							
Finish		Requirements for electroplating are covered in ISO 4042.							
		If different electroplating requirements are desired or if requirements are needed to other finishes, they should be negotiated between supplier and customer.							
Acceptability		The acceptance procedure is covered in ISO 3269.							

¹⁾ Will be covered in a future International Standard.

Designation

Example for the designation of a slotted set screw with cone point, thread size d = M5, nominal length l = 12 mm and property

Set screw ISO 7434 - M5 × 12 - 14H

National appendix (informative)

Mass of set screws

The values given are guideline values.

Thread Vominal Size	M 1,2	M 1,6	M 2	M 2,5	M 3	M 3,5	M 4	M 5	M 6	M 8	M 10	1
ength			-	mixoraa		s (7,85 kg					M 10	M 12
2	0,011	0.020		1		17,00 K	j/Gin°), i	n kg per	1000 un	its		
2,5	0,014	0,026	 -					 				<u> </u>
3	0,017	0,032	0,045	0,07	 	 	 -		ļ	ļ	<u> </u>	<u> </u>
4	0,024	0.046	0.065	0.10	0,13			 		<u> </u>	<u> </u>	
5	0,031	0,060	0.085	0,13	0,17	0,23		 -			├	ļ
6	0,038	0.074	0,11	0,16	0,21	0,29	0.36		ļ	 		
8		0,10	0,14	0.22	0,29	0,40				 	<u> </u>	<u> </u>
10			0.18	0,28	0,29		0,51	0,77	1,04	ļ		
12			<u> </u>	0,26	0,37	0,51	0,66	1,02	1,44	2,65		
14				0.34		0,62	0,82	1,27	1,84	3,25	4,60	
16					0,53	0,73	0.97	1,51	2,24	3,85	5,60	8,35
20					0,61	0,85	1,12	1,76	2,64	4,45	6,60	9,50
25						1,07	1,42	2.25	3,44	5,65	8,60	11,8
30				\longrightarrow				2,88	4,44	7,15	11,1	14,7
35									5,44	8,65	13,6	17,6
40						1				10,2	16,1	20,4
45		+								11,7	18,6	23,3
50		· ‡.									21,1	26,2
55											23,6	29,1
60]				31,9
						- 1		1				34,8