

UDC 621.882.214.2

September 1986

Knurled thumb screws


DIN
464

Randelschrauben, hohe Form



Supersedes December 1970 edition
and DIN 465, December 1970 edition.*In keeping with current practice in standards published by the International Organization for Standardization (ISO), a comma has been used throughout as the decimal marker.*

Dimensions in mm

1 Dimension

Threaded up to the head
(for sizes listed above the stepped line
in the table)Type RAA straight knurl, as specified in DIN 82.
DIN 76 - A thread undercut
DIN 78 - K or DIN 78 - L thread end,
at the manufacturer's discretion.

Type Sz, slotted

With unthreaded portion of shank
(for sizes listed below the stepped line
in the table)Other dimensions and data as for
left-hand illustration.
 $x_1 = 2.5 p$ maximum
(as specified in DIN 76 Part 1).Other dimensions and data
as for illustrations above

Continued on pages 2 to 4

Page 2 DIN 464

Thread size d	M 1	M 1.2	M 1.4	M 1.6	M 2	M 2.5	M 3	(M 3.5)	M 4	M 5	M 6	M 8	M 10
$P^1)$	0,25	0,25	0,3	0,35	0,4	0,45	0,5	0,6	0,7	0,8	1	1,25	1,5
h	3	3,5	4	5	6	8	9	10	12	15	18	24	30
Edges chamfered							0,3	0,3	0,4	0,4	0,5	0,8	0,8
Nominal size	5,5	6	7	7,5	9	11	12	14	16	20	24	30	36
d_k max	5,74	6,24	7,29	7,79	9,29	11,35	12,35	14,35	16,35	20,42	24,42	30,42	36,5
d_k min	5,26	5,76	6,71	7,21	8,71	10,65	11,65	13,65	15,65	19,58	23,58	29,58	35,5
d_k max = nominal size	2,8	3	3,5	3,8	4,5	5	6	7	8	10	12	16	20
d_k min	2,55	2,75	3,2	3,5	4,2	4,7	5,7	6,64	7,64	9,64	11,57	15,57	19,48
Nominal size	3,5	4	4,7	5	5,3	6,5	7,5	8,5	9,5	11,5	15	18	23
h max	3,74	4,24	4,94	5,24	5,54	6,79	7,79	8,79	9,79	11,85	15,35	18,35	23,42
h min	3,26	3,76	4,46	4,76	5,06	6,21	7,21	8,21	9,21	11,15	14,65	17,65	22,58
k max = nominal size	1,5	1,5	2	2	2	2,5	2,5	3	3,5	4	5	6	8
k min	1,25	1,25	1,75	1,75	1,75	2,25	2,25	2,75	3,2	3,7	4,7	5,7	7,64
Nominal size	0,3	0,4	0,4	0,4	0,5	0,6	0,8	0,8	1	1,2	1,6	2	2,5
n min	0,36	0,46	0,46	0,46	0,56	0,66	0,86	0,86	1,06	1,26	1,66	2,06	2,56
n max	0,5	0,6	0,6	0,6	0,7	0,8	1	1	1,2	1,51	1,91	2,31	2,81
r	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5	1	1	2	2
t min	0,7	0,8	0,9	1	1,1	1,5	1,8	2	2,2	2,8	3,5	4,5	6
t max	0,9	1	1,15	1,3	1,4	1,8	2,2	2,5	2,7	3,4	4,3	5,5	7
Mass (7.85 kg/dm ³), in kg per 1000 units, approximately													
Nominal size	min	max											
2	1,9	2,1	0,385	0,485	0,825	0,95							
3	2,9	3,1	0,39	0,492	0,834	0,96	1,45	2,5					
4	3,9	4,1	0,394	0,499	0,843	0,97	1,47	2,53	3,5				
5	4,8	5,2	0,4	0,508	0,852	0,98	1,49	2,56	3,54	5,59	8,28		
6	5,8	6,2			0,864	0,99	1,51	2,59	3,59	5,65	8,36	15,2	
8	7,8	8,2				1,02	1,55	2,65	3,68	5,77	8,51	15,4	28
10	9,7	10,3				1,6	2,71	3,77	5,82	8,68	15,7	28,4	
12	11,7	12,3					2,77	3,86	6,01	8,81	16	28,7	56
(14)	13,7	14,3						4,04	6,13	8,96	16,3	29	56,4
16	15,7	16,3						4,2	6,25	9,1	16,7	29,3	56,8
(18)	17,7	18,3								9,25	17	29,7	57,2
20	19,6	20,4									17,3	30	58
(22)	21,6	22,4										30,3	58,6
25	24,6	25,4										30,8	59,2
(28)	27,6	28,4											59,6
30	29,6	30,4											106
(32)	31,5	32,5											107
35	34,5	35,5											108
(38)	37,5	38,5											110
40	39,5	40,5											112
													114

Sizes and intermediate lengths given in brackets should be avoided if possible.
 Lengths above 40mm shall be graded in 5mm steps.
 Knurled thumb screws are normally manufactured in sizes for which mass values have been specified.
 1) P = pitch of thread (coarse pitch thread).

2 Technical delivery conditions

Material		Steel	Stainless steel	Non-ferrous metal
General requirements		As specified in DIN 267 Part 1.		
Thread	Tolerance class	For sizes up to and including M 1,4: 6h; from size M 1,6: 6g ¹⁾ .		
	Standard	DIN 13 Part 15		
Mechanical properties ⁴⁾	Property class (material)	St = steel ²⁾	A 1-50 or C 4-50	CuZn = copper-zinc alloy ³⁾
	Standard	DIN 1651 ²⁾	DIN 267 Part 11	DIN 267 Part 18
Permissible dimensional deviations and deviations of form	Product grade	For sizes up to and including M 1,4: F; from size M 1,6: A.		
	Standard	DIN 267 Part 6; ISO 4759 Part 1		
Surface finish ⁵⁾		As processed.	Bright.	Bright.
		DIN 267 Part 19 shall apply with regard to permissible surface discontinuities. DIN 267 Part 9 shall apply with regard to electroplating. DIN 50942 shall apply with regard to phosphating of metals.		
Acceptance inspection		DIN 267 Part 5 shall apply with regard to acceptance inspection ⁶⁾ .		

1) Applies only for screws without surface protection. 6g makes it possible for normal coating thicknesses to be applied in accordance with DIN 267 Part 9 with the reference line (h position) not being exceeded. The coating thickness may require a fundamental deviation larger than that specified for the g position, which however may impair the resistance to stripping of the bolt/nut assembly.

2) St = 9 SMnPb 28 K as specified in DIN 1651 or an equivalent steel in terms of strength. This material shall also be used in cases where property class 5.8 is given in existing documentation.

3) CuZn = CU2 or CU3 (as specified in DIN 267 Part 18), at the manufacturer's discretion.

4) Other property classes or materials shall be subject to agreement.

5) R_z 25 or R_z 16 shall apply for the surface roughness, as appropriate, R_z 16 for thread flanks of sizes not exceeding M 5, R_z 40 for thread flanks in the case of machine cut threads exceeding size M 5, and R_z 100 for thread ends.

6) AQL (acceptable quality level) 1 shall apply for major characteristics and AQL 1,5 for minor characteristics, thread size d and the straight knurl being regarded as major characteristics, lengths l and h , collar diameter, d_s , and external diameter, d_k , as minor characteristics.

3 Designation

Designation of an M 5 knurled thumb screw of nominal length $l = 20$ mm, made of steel (St):

Knurled thumb screw DIN 464 – M 5 × 20 – St

Designation of a slotted (Sz) M 5 knurled thumb screw of length $l = 20$ mm, made of steel (St):

Knurled thumb screw DIN 464 – M 5 × 20 – Sz – St

DIN 962 shall apply with regard to the designation of types and designs with additional data to be given when ordering (e.g. "Knurled thumb screw DIN 464 – AM 3 × 16" instead of the previous designation "Knurled thumb screw DIN 464 – M 3 × 16 × 16").

For knurled thumb screws threaded up to the head, with lengths as listed below the stepped line in the table, dimension a_1 as specified in DIN 76 Part 1 shall apply for the distance from the last full form thread to the head.

Note: If knurled thumb screws are manufactured in two parts, these shall be joined so as to ensure that the same torque will be transmitted as in the case of one-piece knurled thumb screws of the same thread size.

Standards referred to

DIN	13 Part 15	ISO metric screw threads; fundamental deviations and tolerances for screw threads of 1 mm and larger
DIN	78 Part 1	Thread run-outs and thread undercuts for ISO metric threads as specified in DIN 13
DIN	78	Thread ends, lengths of projection of thread ends for ISO metric screw threads as defined in DIN 13
DIN	82	Straight knurls
DIN	267 Part 1	Fasteners; technical delivery conditions; general requirements
DIN	267 Part 5	Fasteners; technical delivery conditions; acceptance inspection (modified version of ISO 3269, 1984 edition)
DIN	267 Part 6	Fasteners; technical delivery conditions; types of finish and dimensional accuracy for product grade F
DIN	267 Part 9	Fasteners; technical delivery conditions; components with electroplated coatings
DIN	267 Part 11	Fasteners; technical delivery conditions (with additions to ISO 3506); corrosion-resistant stainless steel fasteners
DIN	267 Part 18	Fasteners; technical delivery conditions; components made of non-ferrous metals
DIN	267 Part 19	Fasteners; technical delivery conditions; surface discontinuities on bolts and screws
DIN	962	Screws, bolts, studs and nuts; designations, types and finishes
DIN	1651	Free cutting steels; technical delivery conditions
DIN	50942	Phosphating of metals; principles, symbols and test methods
ISO	4759 Part 1	Tolerances for fasteners; bolts, screws and nuts with thread diameters between 1,6 (inclusive) and 150 mm (inclusive) and product grades A, B and C

Previous editions

DIN 465: 03.24, 10.43, 07.53, 02.56, 06.63, 12.70.

DIN 464: 03.24, 10.43, 07.53, 02.56, 06.63, 12.70.

Amendments

The following amendments have been made in comparison with the December 1970 edition of the present standard and the December 1970 edition of DIN 465.

- DIN 464 and DIN 465 have been combined into one standard.
- Symbol Sz has been included for the slotted design as specified in DIN 962.
- The content of the standard has been editorially revised and aligned with the basic standards concerned.
- The technical delivery conditions have been amended.
- The previous design m as specified in DIN 267 Part 2, April 1968 edition, has been replaced by product grade F as specified in DIN 267 Part 6 and product grade A as specified in ISO 4759 Part 1.
- Sizes M 1,7, M 2,3 and M 2,6 have been deleted. However, to cater for documents already in existence and spare parts requirements, they can still be ordered in accordance with the December 1970 editions of DIN 464 and DIN 465.
- Property class 5.8 has been replaced by the indication of "St = 9 SMnPb 28 K".

International Patent Classification

F 16 B 35/00