

UDC 621.882.215.091.6

October 1981

Flat countersunk square neck bolts with long square

DIN
605

Senkschrauben mit hohem Vierkantansatz


Supersedes 11.70 edition

As it is current practice in standards published by the International Organization for Standardization (ISO), the comma has been used throughout as a decimal marker.

Dimensions in mm

1 Field of application

This standard specifies flat countersunk square neck bolts with long square, with metric threads M 6, M 8 and M 10, of product grade C.

2 Dimensions, designation

Designation of a flat countersunk square neck bolt with long square, with screw thread $d = M 10$, length $l = 70$ mm and strength category 3.6 or 4.6 (at manufacturer's description):

Flat countersunk bolt DIN 605 – M 10 x 70

Continued on pages 2 to 4

Page 2 DIN 605

| Screw thread d | | | M 6 | | M 8 | | M 10 | |
|--|-------|--------|-------------------------------|---------------|---------------|---------------|---------------|---------------|
| P | 1) | | 1 | | 1,25 | | 1,5 | |
| b | 2) | | 18 | | 22 | | 26 | |
| | 3) | | 24 | | 28 | | 32 | |
| | 4) | | - | | 41 | | 45 | |
| d_k | max. | | 16,55 | | 20,65 | | 24,65 | |
| | min. | | 15,45 | | 19,35 | | 23,35 | |
| d_s 5) | max. | | 6 | | 8 | | 10 | |
| | min. | | 5,52 | | 7,42 | | 9,42 | |
| f | max. | | 7,45 | | 9,45 | | 11,55 | |
| | min. | | 6,55 | | 8,55 | | 9,45 | |
| r 4) | max. | | 0,9 | | 1,2 | | 1,5 | |
| v 5) | max. | | 6,48 | | 8,58 | | 10,58 | |
| | min. | | 5,52 | | 7,42 | | 9,42 | |
| l | | | Shank lengths l_s and l_g | | | | | |
| Nominal size | min. | max. | l_s min. | l_g max. | l_s min. | l_g max. | l_s min. | l_g max. |
| 30 | 28,95 | 31,05 | - | 12,5 | - | 16 | - | - |
| 35 | 33,75 | 36,25 | - | 12,5 | - | 16 | - | - |
| 40 | 38,75 | 41,25 | 17 | 22 | - | 16 | - | 18 |
| 45 | 43,75 | 46,25 | 22 | 27 | 16,75 | 23 | - | 18 |
| 50 | 48,75 | 51,25 | 27 | 32 | 21,75 | 28 | 16,5 | 24 |
| 55 | 53,5 | 56,5 | 32 | 37 | 26,75 | 33 | 21,5 | 29 |
| 60 | 58,5 | 61,5 | 37 | 42 | 31,75 | 38 | 26,5 | 34 |
| 65 | 63,5 | 66,5 | | | 36,75 | 43 | 31,5 | 39 |
| 70 | 68,5 | 71,5 | | | 41,75 | 48 | 36,5 | 44 |
| 80 | 78,5 | 81,5 | | | 51,75 | 58 | 46,5 | 54 |
| 90 | 88,75 | 91,75 | | | | | 56,5 | 64 |
| 100 | 98,25 | 101,75 | | | | | 66,5 | 74 |
| <p>Lengths exceeding 100 mm must be graded by steps of 10 mm.</p> <p>The commercial lengths are indicated by their shank lengths.</p> <p>Intermediate lengths should be avoided wherever possible.</p> <p>1) P = thread pitch</p> <p>2) For $l \leq 125$ mm</p> <p>3) For $125 < l \leq 200$ mm</p> <p>4) For $l > 200$ mm</p> <p>5) For manufacturing reasons the + IT 15 tolerance is permissible for a length of $2d$ below head (including square). Therefore, the corresponding limiting dimension is given for v max. The shank diameter may also be \approx pitch diameter at manufacturer's discretion.</p> <p>6) Radius r must be adhered to for a minimum length of $0,5$ the square length below the head.</p> | | | | | | | | |

If flat countersunk bolts according to this standard are to be supplied in strength categories 3.6 or 4.6 with hexagon nuts of strength category 5 according to DIN 555, the symbol Mu must be added to the designation, e.g.:

Flat countersunk bolt DIN 605 – M 10 X 70 – Mu

DIN 962 specifies additional forms, types and details of order, as far as the said standard is applicable to flat countersunk bolts.

3 Technical delivery conditions

| Material | | Steel |
|---|---|---|
| General requirements | | according to DIN 267 Part 1 |
| Screw thread | tolerance | 8 g |
| | standard | DIN 13 Part 13 |
| Mechanical properties | strength category ¹⁾ | 3.6 or 4.6 at manufacturer's discretion |
| | standard | DIN ISO 898 Part 1 |
| Permissible dimensional deviations | product grade | C (previous type g) |
| | standard | DIN ISO 4759 Part 1 |
| Surface | DIN 267 Part 2 applies to the peak-to-valley heights of surfaces permissible surface defects according to DIN 267 Part 19 galvanic surface protection according to DIN 267 Part 9 hot-dip galvanizing according to DIN 267 Part 10 | |
| Acceptance testing | according to DIN 267 Part 5 | |
| ¹⁾ If a specific strength category is required this must be indicated in the designation, e.g.: Flat countersunk bolt DIN 605 – M 10 X 70 – 4.6 | | |

4 Weights

The weights listed are reference values.

| Screw thread <i>d</i> | M 6 | M 8 | M 10 |
|-----------------------|--|------|------|
| Length <i>l</i> | Weight (7,85 kg/dm ³) kg/1000 pieces ≈ | | |
| 30 | 8,80 | 15,4 | |
| 35 | 9,80 | 17,4 | |
| 40 | 10,8 | 19,3 | 30,6 |
| 45 | 11,9 | 21,3 | 33,6 |
| 50 | 12,9 | 23,2 | 36,5 |
| 55 | 13,9 | 25,2 | 39,4 |
| 60 | 14,9 | 27,1 | 42,4 |
| 65 | | 29,1 | 45,3 |
| 70 | | 31,0 | 48,2 |
| 80 | | 34,9 | 54,1 |
| 90 | | | 59,9 |
| 100 | | | 65,7 |

Page 4 DIN 605

Standards referred to

| | |
|---------------------|---|
| DIN 13 Part 13 | ISO metric screw thread; review of screw threads for bolts and nuts from 1 to 52 mm thread diameter and limiting sizes |
| DIN 267 Part 1 | Bolts, screws, nuts and similar threaded and formed parts; technical conditions of delivery; general information |
| DIN 267 Part 2 | Bolts, screws, nuts and similar threaded and formed parts; technical conditions of delivery; types and dimensional accuracy |
| DIN 267 Part 5 | Bolts, screws, nuts and similar threaded and formed parts; technical conditions of delivery; testing and accepting |
| DIN 267 Part 9 | Mechanical fasteners; technical conditions of delivery; components with electroplated coatings |
| DIN 267 Part 10 | Fasteners; technical conditions of delivery; hot-dip galvanized parts |
| DIN 267 Part 19 | Fasteners; technical conditions of delivery; surface defects of screws |
| DIN 555 | Hexagon nuts; metric thread, type g |
| DIN 962 | Screws, bolts, studs and nuts; additional types and finishes; details of order and dimensions |
| DIN ISO 272 | Fasteners, hexagon products, widths across flats |
| DIN ISO 898 Part 1 | Mechanical properties of fasteners; bolts, screws and studs |
| DIN ISO 4759 Part 1 | Tolerances for fasteners; bolts, screws and nuts with thread diameters between 1,6 (inclusive) and 150 mm (inclusive) and product grades A, B and C |

Former editions

DIN 566: 02.23, 04.26, 04.36; DIN 566 Supplement: 10.26; DIN 605 Part 1: 01.41, 05.53, 12.55, 03.63;
 DIN 605: 10.26, 07.36, 12.67, 11.70

Amendments

Compared with the November 1970 edition the following amendments and additions have been made in this revised edition of DIN 605:

- a) The "with hexagon nut according to DIN 555" type is no longer contained in the representation of the flat counter-sunk bolt. However, this type may still be ordered as part of this standard according to clause 2.
- b) The dimensioning of the bolts was changed. The shank lengths l_s and l_g were adopted, l_g max. indicating at the same time the minimum grip of the bolts. The former screw thread length b is just a reference dimension for calculating l_s and l_g . The difference between l_s min. and l_g max. is $5 \times$ thread pitch, this value including the screw thread runout and the tolerances on length. In the case of shorter bolts l_g max. = f max. + $5 P$, with l_s falling in this range, i.e. these bolts have a thread almost reaching the square. This new kind of dimensioning does not adversely affect interchangeability (new for old), because the screw thread length b , taken as a basis for calculating l_s and l_g , was not changed.
- c) The limits of the individual dimensions were adopted. They have regard to the tolerances according to DIN ISO 4759 Part 1, but this does not cause any significant changes as compared with the previous tolerances of DIN 267 Part 2.
- d) New limiting dimensions resulting from DIN 267 Part 2 were specified for the square taking into account the permissible upseting which corresponds to $+IT 15$ within a length of $2d$ below head. The present specifications in DIN 267 Part 2 are not quite clear in this respect.
- e) The bolt weights were specified separately, the previous weights being reduced by the weights of the nuts.
- f) The strength categories refer to DIN ISO 898 Part 1. This standard supersedes DIN 267 Part 3.
 The strength categories 3.6 and 4.6 apply as usual. It is not intended to differentiate between 3.6 and 4.6, because this limit depends on the manufacturing process.
- g) Details concerning the type were adapted to DIN ISO 4759 Part 1. This standard partly supersedes DIN 267 Part 2. It was not possible to completely dispense with DIN 267 Part 2 in favour of DIN ISO 4759 Part 1, because, e.g., the DIN ISO Standard does not contain any details on the surfaces (peak-to-valley heights). Apart from this, product grades A, B and C of DIN ISO 4759 Part 1 are practically identical with the previous types m, mg and g according to DIN 267 Part 2. Therefore, in this case, type g could be replaced easily by product grade C.
- h) The previous "edges of square radiused" type was replaced by adopting a maximum value for the rounding radius.
- i) Sizes M 5, M 12, M 16 and M 20 were deleted, because they have been used in exceptional cases only.