

UDC 621.882.215.1.091.6.092.4

September 1986

# Slotted countersunk head screws with full dog point

**DIN**  
**925**

Senkschrauben mit Schlitz und Zapfen


Superseries August 1972 edition

In keeping with current practice in standards published by the International Organization for Standardization (ISO), a comma has been used throughout as the decimal marker

## 1 Dimensions

Dimensions in mm

$$\sqrt{\quad} = \begin{cases} \sqrt{R_2 6,3} & \text{for sizes up to M3} \\ \sqrt{R_2 16} & \text{for sizes exceeding M3} \end{cases}$$



$a_2$  as specified in  
DIN 76 Part I  
(2 P maximum)

Thread size $d$		M 1,4	M 1,6	M 2	M 2,5	M 3
$d_k$	max = nominal size	0,3	0,35	0,4	0,45	0,5
	min	2,6	3	3,8	4,7	5,6
$d_p$	max = nominal size	0,8	0,8	1,2	1,5	2
	min	0,775	0,775	1,175	1,475	1,975
$l$	max	0,84	0,96	1,2	1,5	1,65
	min	0,3	0,4	0,5	0,5	0,8
$r$	max	0,36	0,46	0,56	0,66	0,86
	min	0,5	0,6	0,7	0,8	1
$t$	max	0,14	0,16	0,2	0,25	0,3
	min	0,28	0,32	0,4	0,5	0,6
$z$	max	0,4	0,45	0,6	0,7	0,85
	min	0,2	0,2	0,25	0,35	0,4
$l_1$						
Nominal size	Tolerance					
1,6	js 15 for $l_1$ and $l_2$ .					
2						
2,5						
(3)						
4						
(5)						
6						
$l_2$						
Nominal size	min	max				
0,6	0,5	0,85				
(0,8)	0,8	1,05				
1	1	1,25				
(1,2)	1,2	1,45				
1,6	1,6	1,95				
2	2	2,25				
2,5	2,5	2,75				
(3)	3	3,25				

Lengths  $l_1$  and  $l_2$  and intermediate lengths given in brackets should be avoided if possible.  
Slotted countersunk head screws are normally manufactured in the range indicated by stepped lines.  
<sup>1)</sup> P = pitch of thread (coarse pitch thread)

Continued on pages 2 and 3

**2 Technical delivery conditions**

Material		Steel	Stainless steel	Non-ferrous metal
General requirements		As specified in DIN 267 Part 1.		
Thread	Tolerance class	For size M1.4: 4 h, from size M1.6: 6 g.		
	Standard	DIN 13 Part 15		
Mechanical properties <sup>3)</sup>	Property class (material)	5.8 <sup>1)</sup>	A1-50 C4-50	CuZn = copper-zinc alloy <sup>2)</sup>
	Standard	ISO 898 Part 1 (test programme B)	DIN 267 Part 11	DIN 267 Part 18
Permissible dimensional deviations and deviations of form	Product grade	For size M1.4: F, from size M1.6: A.		
	Standard	DIN 267 Part 6; ISO 4759 Part 1		
Types and finishes with additional information to be stated on ordering		As specified in DIN 962.		
Surface finish		As processed.	Bright	Bright.
		DIN 267 Part 2 shall apply with regard to surface roughness. DIN 267 Part 19 shall apply with regard to permissible surface discontinuities. DIN 267 Part 9 shall apply with regard to electroplating.		
Acceptance inspection		DIN 267 Part 5 shall apply with regard to acceptance inspection.		

<sup>1)</sup> Where cold drawn steels as specified in DIN 1651 are used, an elongation at break,  $A_5$ , of 5% shall be permissible.  
<sup>2)</sup> CuZn = CU2 or CU3 (as specified in DIN 267 Part 18), at the manufacturer's discretion.  
<sup>3)</sup> Other property classes or materials shall be subject to agreement.

**3 Designation**

Designation of an M2 slotted countersunk head screw with full dog point, of lengths  $l_1 = 2,5$  mm and  $l_2 = 1,6$  mm, assigned to property class 5.8<sup>1)</sup>:

Countersunk head screw DIN 925 – M2 × 2,5 × 1,6 – 5.8

<sup>1)</sup> Where no property class or type of material is given in existing documentation, property class 5.8 shall apply.

**Standards referred to**

DIN 13 Part 15	ISO metric screw threads; fundamental deviations and tolerances for screw threads of 1 mm and larger
DIN 76 Part 1	Thread run-outs and thread undercuts for ISO metric threads as specified in DIN 13
DIN 267 Part 1	Fasteners; technical delivery conditions; general requirements
DIN 267 Part 2	Fasteners; technical delivery conditions; types of finish and dimensional accuracy
DIN 267 Part 5	Fasteners; technical delivery conditions; acceptance inspection (modified version of ISO 3269, 1984 edition)
DIN 267 Part 6	Fasteners; technical delivery conditions; types of finish and dimensional accuracy for product grade F
DIN 267 Part 9	Fasteners; technical delivery conditions; components with electroplated coatings
DIN 267 Part 11	Fasteners; technical delivery conditions (with additions to ISO 3506); corrosion-resistant stainless steel fasteners
DIN 267 Part 18	Fasteners; technical delivery conditions; components made of non-ferrous metals
DIN 267 Part 19	Fasteners; technical delivery conditions; surface discontinuities on bolts and screws
DIN 962	Screws, bolts, studs and nuts; designations, types and finishes
DIN 1651	Free cutting steels; technical delivery conditions
ISO 898 Part 1	Mechanical properties of fasteners; bolts, screws and studs
ISO 4759 Part 1	Tolerances for fasteners; bolts, screws and nuts with thread diameters between 1,6 (inclusive) and 150 mm (inclusive) and product grades A, B and C

**Previous editions**

01.43, 08.53, 08.72.

**Amendments**

The following amendments have been made in comparison with the August 1972 edition.

- a) Size M 1,8 has been deleted because there is no demand for it.
- b) The previous design m as specified in DIN 267 Part 2, April 1968 edition, has been replaced by product grade F as specified in DIN 267 Part 6 and product grade A as specified in ISO 4759 Part 1.
- c) Limiting dimensions calculated from the permissible tolerances have been included.
- d) The technical delivery conditions have been amended.
- e) The content of the standard has been editorially revised.
- f) The example of designation has been amended.

**International Patent Classification**

F 16 B 23/00

F 16 B 35/00