UDC 621.886.2

April 1973

Round lost head wire nails


<u>DIN</u> 1152

Drahtstifte, rund, Stauchkopf

In keeping with current practice in standards published by the International Organization for Standardization (ISO), a comma has been used throughout as the decimal marker.

Dimensions in mm

Details left unspecified are to be selected as appropriate.



Designation of a round lost head wire nail of size 12 × 20, with bright finish (bk):

Nail 12 × 20 DIN 1152 - bk

Size	d		ì	Net weight of pack,
		Limit deviations*)	± 1 d	in kg
10× 15	1	±0,04	15	1
12× 20	1,2	±0,04	20	1
14 × 25	1,4	±0,04	25	1
16× 30	1,6	±0,06	30	1
18× 35	1,8	±0.06	35	2,5
20 × 40	2	±0,06	40	2,5
22 × 45	2,2	±0,06	45	2,5
22× 50	2,2	±0,06	50	2,5
22 × 55	2,2	±0,06	55	2,5
25 × 55	2,5	±0,08	55	2,5
25 × 60	2,5	±0,08	60	2,5
28 × 65	2,8	±0,08	65	2,5
31 × 80	3,1	±0,08	80	5
34 × 90	3,4	±0,08	90	5
38 × 100	3,8	±0.08	100	5

Material and finish

Wire nails shall be made of steel (grade at manufacturer's discretion) and have a bright (bk)1) or galvanized (zn)1) finish.

Form of supply

Wire nails shall be supplied in packs.

Designation for ordering 100 kg of round lost head wire nails of size 12 × 20, with bright finish (bk):

100 kg nalis 12 × 20 DiN 1152 ~ bk

¹⁾ Symbol as in DIN 1653.