Aug 17 2001 9:20

P. 01/01

UDC 621.882.249.4 : 621.882.3

September 1965


Screwed Inserts (Screw Plugs)

Fax:062084389

DIN 7965

Einschraubmuttern (Schraubdübel)

These acrewed inserts are intended primarily for screwing into wood or wood-like materials.



Designation of a screwed insert with thread  $d_4$  = M 6 and length  $l_4$  = 15 mm, in St: Screwed insert M 6 x 15 DIN 7965 - St

Thread d <sub>1</sub>	МЗ	M 4	M 5	М 6	М8	M 10	M 12	M 16	M 20
d <sub>2</sub>	6	8	- 10	12	. 16	18,5	22	25	29
d <sub>3</sub>	4,5	5,5	7,5	9,5	12,5	15	18	20,5	24
d <sub>4</sub>	3,5	4,5	6	7,5	10 -	12	15	17,5	21
d <sub>5</sub>	- 5	6,5	8,5	10,5	14,5	17	20	22,5	26
h	2	2,5	3,5	4	5	5	5	5	5
12	5	6	7	9	11	13 ~	16	16	20
n	1	1,2	1,6	2	2,5	3	3	4	5
ŧ	2	2	3	3	4	- 5	5	6	6
Z	0,6	0,6	0,8	1	1	1,6	1,6	1,6	1,6
Length /	1					·			<del></del>
8	×								l
10		×							
12		·	×						
15				×	1				
18					×			1	
20									}
25						×			1
30							×	×	×
40				]					
50	T								

x = Preferred sizes

Material (to be indicated when ordering):

Bt - Steel

Ms = Brass Al-Leg. = Aluminium alloy

Type1 mg according to DIN 267

Correlation of holes

Predrilled hole